



INDOOR PHOTOMETRIC REPORT

CATALOG: LUX-IK10P-E-2-SA-HO3-850-2-U10-CA2

MANUFACTURER: LUX DYNAMICS
TEST #: L051800502
TEST LAB: LIGHT LABORATORY, INC. (WWW.LIGHTLABORATORY.COM)
CATALOG: LUX-IK10P-E-2-SA-HO3-850-2-U10-CA2
DESCRIPTION: 2-BAR, 1-CHANNEL, HIGH EFFICACY, ACRYLIC LENS, 2'
LAMP OUTPUT: TOTAL LUMINAIRE LUMENS: 12312.1, **ABSOLUTE PHOTOMETRY ***
BALLAST / DRIVER: OSRAM OPTOTRONIC OTI 85/120-277/2A3 DIM L
INPUT WATTAGE: 77.7
LUMINOUS OPENING: RECTANGLE (L: 22.92", W: 11.52")
CIE CLASS: DIRECT
MAX CD: 4,163.0 AT HORIZONTAL: 85°, VERTICAL: 15°



***TEST BASED ON ABSOLUTE PHOTOMETRY WHERE LAMP LUMENS=LUMENS TOTAL.**

***CUTOFF CLASSIFICATION AND EFFICIENCY CANNOT BE PROPERLY CALCULATED FOR ABSOLUTE PHOTOMETRY.**

VISUAL PHOTOMETRIC TOOL 1.2.46 COPYRIGHT 2018, ACUITY BRANDS LIGHTING.

THIS PHOTOMETRIC REPORT HAS BEEN GENERATED USING METHODS RECOMMENDED BY THE IESNA. CALCULATIONS ARE BASED ON PHOTOMETRIC DATA PROVIDED BY THE MANUFACTURER, AND THE ACCURACY OF THIS PHOTOMETRIC REPORT IS DEPENDENT ON THE ACCURACY OF THE DATA PROVIDED. END-USER ENVIRONMENT AND APPLICATION (INCLUDING, BUT NOT LIMITED TO, VOLTAGE VARIATION AND DIRT ACCUMULATION) CAN CAUSE ACTUAL PHOTOMETRIC PERFORMANCE TO DIFFER FROM THE PERFORMANCE CALCULATED USING THE DATA PROVIDED BY THE MANUFACTURER. THIS REPORT IS PROVIDED WITHOUT WARRANTY AS TO ACCURACY, COMPLETENESS, RELIABILITY OR OTHERWISE. IN NO EVENT WILL ACUITY BRANDS LIGHTING BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF THIS REPORT.

INDOOR PHOTOMETRIC REPORT

CATALOG: LUX-IK10P-E-2-SA-HO3-850-2-U10-CA2

ZONAL LUMEN SUMMARY

ZONE	LUMENS	% LUMINAIRE
0-30	3,204.1	26%
0-40	5,160.4	41.9%
0-60	8,964.9	72.8%
60-90	2,778.0	22.6%
70-100	1,376.5	11.2%
90-120	293.9	2.4%
0-90	11,742.9	95.4%
90-180	569.2	4.6%
0-180	12,312.1	100%

LUMENS PER ZONE

ZONE	LUMENS	% TOTAL	ZONE	LUMENS	% TOTAL
0-10	386.8	3.1%	90-100	128.0	1%
10-20	1,128.3	9.2%	100-110	85.6	0.7%
20-30	1,688.9	13.7%	110-120	80.3	0.7%
30-40	1,956.3	15.9%	120-130	82.9	0.7%
40-50	1,953.0	15.9%	130-140	76.1	0.6%
50-60	1,851.5	15.0%	140-150	57.7	0.5%
60-70	1,529.6	12.4%	150-160	37.7	0.3%
70-80	914.5	7.4%	160-170	16.8	0.1%
80-90	333.9	2.7%	170-180	4.1	0%

LCS TABLE

BUG RATING

B3 - U3 - G2

FORWARD LIGHT

LUMENS LUMENS %

LOW(0-30):	1,602.8	13%
MEDIUM(30-60):	2,881.6	23.4%
HIGH(60-80):	1,222.5	9.9%
VERY HIGH(80-90):	167.0	1.4%

BACK LIGHT

LOW(0-30):	1,602.8	13%
MEDIUM(30-60):	2,881.6	23.4%
HIGH(60-80):	1,222.5	9.9%
VERY HIGH(80-90):	167.0	1.4%

UPLIGHT

LOW(90-100):	128.0	1%
HIGH(100-180):	441.0	3.6%

TRAPPED LIGHT: 0.000 0%

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

EFFECTIVE FLOOR CAVITY REFLECTANCE: 20%

RCC %:	80				70				50				30				10				0
RW %:	70	50	30	0	70	50	30	0	50	30	20	50	30	20	50	30	20	50	30	20	0
RCR: 0	1.18	1.18	1.18	1.18	1.15	1.15	1.15	.95	1.09	1.09	1.09	1.03	1.03	1.03	.98	.98	.98	.95		.95	
1	1.07	1.02	.98	.94	1.04	.99	.95	.80	.94	.91	.88	.90	.87	.84	.85	.83	.81	.79		.79	
2	.97	.89	.82	.76	.94	.86	.80	.66	.82	.77	.72	.78	.74	.70	.74	.71	.68	.65		.65	
3	.88	.78	.69	.63	.86	.76	.68	.56	.72	.66	.60	.69	.63	.59	.66	.61	.57	.55		.55	
4	.81	.69	.60	.53	.78	.67	.59	.48	.64	.57	.51	.61	.55	.50	.58	.53	.49	.46		.46	
5	.74	.61	.52	.46	.72	.60	.51	.42	.57	.50	.44	.55	.48	.43	.53	.47	.42	.40		.40	
6	.69	.55	.46	.40	.66	.54	.46	.37	.52	.44	.39	.50	.43	.38	.48	.42	.37	.35		.35	
7	.64	.50	.41	.35	.62	.49	.41	.33	.47	.40	.34	.45	.39	.34	.44	.38	.33	.31		.31	
8	.59	.46	.37	.31	.57	.45	.37	.29	.43	.36	.31	.42	.35	.30	.40	.34	.30	.28		.28	
9	.55	.42	.34	.28	.54	.41	.33	.27	.40	.33	.28	.38	.32	.27	.37	.31	.27	.25		.25	
10	.52	.39	.31	.26	.50	.38	.30	.24	.37	.30	.25	.35	.29	.25	.34	.29	.24	.23		.23	

INDOOR PHOTOMETRIC REPORT
 CATALOG: LUX-IK10P-E-2-SA-HO3-850-2-U10-CA2

