



INDOOR PHOTOMETRIC REPORT

CATALOG: LUX-IK10P-E-8-TA-HO3-850-2-U10-CA2

MANUFACTURER: LUX DYNAMICS
TEST #: L051800508
TEST LAB: LIGHT LABORATORY, INC. (WWW.LIGHTLABORATORY.COM)
CATALOG: LUX-IK10P-E-8-TA-HO3-850-2-U10-CA2
DESCRIPTION: 8-BAR, 3-CHANNEL, HIGH EFFICACY, ACRYLIC LENS, 2'
LAMP OUTPUT: TOTAL LUMINAIRE LUMENS: 48452.5, ABSOLUTE PHOTOMETRY *
BALLAST / DRIVER: OSRAM OPTOTRONIC OTI 85/120-277/2A3 DIM L (4 DRIVERS)
INPUT WATTAGE: 311.44
LUMINOUS OPENING: RECTANGLE (L: 29.52", W: 20.52")
CIE CLASS: DIRECT
MAX CD: 16,620.0 AT HORIZONTAL: 0°, VERTICAL: 0°



*TEST BASED ON ABSOLUTE PHOTOMETRY WHERE LAMP LUMENS=LUMENS TOTAL.
*CUTOFF CLASSIFICATION AND EFFICIENCY CANNOT BE PROPERLY CALCULATED FOR ABSOLUTE PHOTOMETRY.

VISUAL PHOTOMETRIC TOOL 1.2.46 COPYRIGHT 2018, ACUITY BRANDS LIGHTING.
THIS PHOTOMETRIC REPORT HAS BEEN GENERATED USING METHODS RECOMMENDED BY THE IESNA. CALCULATIONS ARE BASED ON PHOTOMETRIC DATA PROVIDED BY THE MANUFACTURER, AND THE ACCURACY OF THIS PHOTOMETRIC REPORT IS DEPENDENT ON THE ACCURACY OF THE DATA PROVIDED. END-USER ENVIRONMENT AND APPLICATION (INCLUDING, BUT NOT LIMITED TO, VOLTAGE VARIATION AND DIRT ACCUMULATION) CAN CAUSE ACTUAL PHOTOMETRIC PERFORMANCE TO DIFFER FROM THE PERFORMANCE CALCULATED USING THE DATA PROVIDED BY THE MANUFACTURER. THIS REPORT IS PROVIDED WITHOUT WARRANTY AS TO ACCURACY, COMPLETENESS, RELIABILITY OR OTHERWISE. IN NO EVENT WILL ACUITY BRANDS LIGHTING BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF THIS REPORT.

ZONAL LUMEN SUMMARY

ZONE	LUMENS	% LUMINAIRE
0-30	12,771.0	26.4%
0-40	20,663.2	42.6%
0-60	36,147.2	74.6%
60-90	10,658.7	22%
70-100	4,511.8	9.3%
90-120	365.7	0.8%
0-90	46,805.9	96.6%
90-180	1,646.6	3.4%
0-180	48,452.5	100%

LUMENS PER ZONE

ZONE	LUMENS	% TOTAL	ZONE	LUMENS	% TOTAL
0-10	1,555.1	3.2%	90-100	81.5	0.2%
10-20	4,476.9	9.2%	100-110	103.7	0.2%
20-30	6,739.0	13.9%	110-120	180.5	0.4%
30-40	7,892.2	16.3%	120-130	311.9	0.6%
40-50	7,941.4	16.4%	130-140	378.8	0.8%
50-60	7,542.6	15.6%	140-150	291.5	0.6%
60-70	6,228.5	12.9%	150-160	191.7	0.4%
70-80	3,531.9	7.3%	160-170	85.9	0.2%
80-90	898.3	1.9%	170-180	21.1	0%

LCS TABLE

BUG RATING

B5 - U5 - G3

FORWARD LIGHT	LUMENS	LUMENS %
LOW(0-30):	6,388.5	13.2%
MEDIUM(30-60):	11,693.0	24.1%
HIGH(60-80):	4,882.0	10.1%
VERY HIGH(80-90):	449.3	0.9%
BACK LIGHT		
LOW(0-30):	6,388.5	13.2%
MEDIUM(30-60):	11,693.0	24.1%
HIGH(60-80):	4,882.0	10.1%
VERY HIGH(80-90):	449.3	0.9%
UPLIGHT		
LOW(90-100):	81.5	0.2%
HIGH(100-180):	1,564.8	3.2%
TRAPPED LIGHT:	0.000	0%

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

EFFECTIVE FLOOR CAVITY REFLECTANCE: 20%

RCC %:	80				70				50				30				10				0
RW %:	70	50	30	0	70	50	30	0	50	30	20	0	50	30	20	0	50	30	20	0	
RCR: 0	1.18	1.18	1.18	1.18	1.15	1.15	1.15	.97	1.09	1.09	1.09	1.04	1.04	1.04	.99	.99	.99	.97			
1	1.08	1.03	.99	.95	1.05	1.00	.96	.81	.95	.92	.89	.91	.88	.86	.87	.85	.83	.80			
2	.98	.89	.82	.77	.95	.87	.81	.68	.83	.78	.73	.79	.75	.71	.76	.72	.69	.67			
3	.89	.78	.70	.63	.86	.76	.69	.57	.73	.66	.61	.70	.64	.60	.67	.62	.58	.56			
4	.81	.69	.60	.54	.79	.68	.59	.49	.65	.58	.52	.62	.56	.51	.59	.54	.50	.48			
5	.75	.62	.53	.46	.72	.60	.52	.43	.58	.51	.45	.56	.49	.44	.53	.48	.43	.41			
6	.69	.56	.47	.40	.67	.54	.46	.38	.52	.45	.39	.50	.44	.39	.48	.43	.38	.36			
7	.64	.50	.42	.35	.62	.49	.41	.33	.48	.40	.35	.46	.39	.34	.44	.38	.34	.32			
8	.60	.46	.37	.32	.58	.45	.37	.30	.44	.36	.31	.42	.35	.31	.41	.35	.30	.28			
9	.56	.42	.34	.28	.54	.41	.34	.27	.40	.33	.28	.39	.32	.28	.38	.32	.27	.25			
10	.52	.39	.31	.26	.51	.38	.31	.25	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23			

