


INDOOR PHOTOMETRIC REPORT

CATALOG: LUX-IK10P-L-4-DA-HO3-850-2-U10-CA2

MANUFACTURER: LUX DYNAMICS
TEST #: L051805402
TEST LAB: LIGHT LABORATORY, INC. (WWW.LIGHTLABORATORY.COM)
CATALOG: LUX-IK10P-L-4-DA-HO3-850-2-U10-CA2
DESCRIPTION: 4-BAR, 2-CHANNEL, HIGH LUMEN, ACRYLIC LENS, 2'
LAMP OUTPUT: TOTAL LUMINAIRE LUMENS: 44546.9, **ABSOLUTE PHOTOMETRY ***
BALLAST / DRIVER: OSRAM OPTOTRONIC OTI 85/120-277/2A3 DIM L (4 DRIVERS)
INPUT WATTAGE: 326.55
LUMINOUS OPENING: RECTANGLE (L: 23.04", W: 11.28")
CIE CLASS: DIRECT
MAX CD: 15,553.0 AT HORIZONTAL: 0°, VERTICAL: 0°



***TEST BASED ON ABSOLUTE PHOTOMETRY WHERE LAMP LUMENS=LUMENS TOTAL.
*CUTOFF CLASSIFICATION AND EFFICIENCY CANNOT BE PROPERLY CALCULATED FOR ABSOLUTE PHOTOMETRY.**

VISUAL PHOTOMETRIC TOOL 1.2.46 COPYRIGHT 2018, ACUITY BRANDS LIGHTING.
THIS PHOTOMETRIC REPORT HAS BEEN GENERATED USING METHODS RECOMMENDED BY THE IESNA. CALCULATIONS ARE BASED ON PHOTOMETRIC DATA PROVIDED BY THE MANUFACTURER, AND THE ACCURACY OF THIS PHOTOMETRIC REPORT IS DEPENDENT ON THE ACCURACY OF THE DATA PROVIDED. END-USER ENVIRONMENT AND APPLICATION (INCLUDING, BUT NOT LIMITED TO, VOLTAGE VARIATION AND DIRT ACCUMULATION) CAN CAUSE ACTUAL PHOTOMETRIC PERFORMANCE TO DIFFER FROM THE PERFORMANCE CALCULATED USING THE DATA PROVIDED BY THE MANUFACTURER. THIS REPORT IS PROVIDED WITHOUT WARRANTY AS TO ACCURACY, COMPLETENESS, RELIABILITY OR OTHERWISE. IN NO EVENT WILL ACUITY BRANDS LIGHTING BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF THIS REPORT.

ZONAL LUMEN SUMMARY

ZONE	LUMENS	% LUMINAIRE
0-30	11,938.9	26.8%
0-40	19,254.3	43.2%
0-60	33,514.2	75.2%
60-90	9,457.6	21.2%
70-100	3,928.6	8.8%
90-120	350.1	0.8%
0-90	42,971.8	96.5%
90-180	1,575.2	3.5%
0-180	44,546.9	100%

LUMENS PER ZONE

ZONE	LUMENS	% TOTAL	ZONE	LUMENS	% TOTAL
0-10	1,457.4	3.3%	90-100	79.1	0.2%
10-20	4,198.6	9.4%	100-110	101.2	0.2%
20-30	6,282.9	14.1%	110-120	169.8	0.4%
30-40	7,315.4	16.4%	120-130	292.0	0.7%
40-50	7,328.8	16.5%	130-140	349.2	0.8%
50-60	6,931.1	15.6%	140-150	283.5	0.6%
60-70	5,608.1	12.6%	150-160	195.8	0.4%
70-80	3,098.5	7.0%	160-170	85.3	0.2%
80-90	751.0	1.7%	170-180	19.2	0%

LCS TABLE

BUG RATING

B5 - U5 - G3

FORWARD LIGHT	LUMENS	LUMENS %
LOW(0-30):	5,972.3	13.4%
MEDIUM(30-60):	10,792.3	24.2%
HIGH(60-80):	4,355.0	9.8%
VERY HIGH(80-90):	375.6	0.8%
BACK LIGHT		
LOW(0-30):	5,972.3	13.4%
MEDIUM(30-60):	10,792.3	24.2%
HIGH(60-80):	4,355.0	9.8%
VERY HIGH(80-90):	375.6	0.8%
UPLIGHT		
LOW(90-100):	79.1	0.2%
HIGH(100-180):	1,495.9	3.4%
TRAPPED LIGHT:	0.000	0%

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

EFFECTIVE FLOOR CAVITY REFLECTANCE: 20%

RCC %:	80				70				50				30				10				0
RW %:	70	50	30	0	70	50	30	0	50	30	20	0	50	30	20	0	50	30	20	0	
RCR: 0	1.18	1.18	1.18	1.18	1.15	1.15	1.15	.96	1.09	1.09	1.09	1.04	1.04	1.04	.99	.99	.99	.96			
1	1.08	1.03	.99	.95	1.05	1.00	.97	.81	.96	.92	.89	.91	.88	.86	.87	.85	.83	.81			
2	.98	.90	.83	.77	.95	.88	.81	.68	.83	.78	.74	.80	.75	.71	.76	.72	.69	.67			
3	.89	.79	.70	.64	.86	.77	.69	.58	.73	.67	.62	.70	.65	.60	.67	.63	.59	.56			
4	.82	.70	.61	.54	.79	.68	.60	.50	.65	.58	.52	.62	.56	.51	.60	.55	.50	.48			
5	.75	.62	.53	.47	.73	.61	.52	.43	.58	.51	.45	.56	.50	.44	.54	.48	.44	.41			
6	.69	.56	.47	.41	.67	.55	.46	.38	.53	.45	.40	.51	.44	.39	.49	.43	.38	.36			
7	.64	.51	.42	.36	.62	.50	.41	.34	.48	.40	.35	.46	.40	.35	.45	.39	.34	.32			
8	.60	.46	.38	.32	.58	.45	.37	.30	.44	.37	.31	.42	.36	.31	.41	.35	.31	.29			
9	.56	.43	.34	.29	.54	.42	.34	.27	.40	.33	.28	.39	.33	.28	.38	.32	.28	.26			
10	.52	.39	.31	.26	.51	.39	.31	.25	.37	.30	.26	.36	.30	.25	.35	.29	.25	.23			

